Introduction :

First here is a look of Sablure Exulium :



And here is a look of the time extractor (ExtraCTuM),



Customization:
1- ChronoX

When you start Exulium, here is a WokLaB button wich open the WokLaB Folder
From here there is the StylisT Folder and a StylisT File.

In this File you will define the name of your ChronoX : <Poste Nam= contain the begin of the name of the file wich retain actions and time, here, the place is named FHDMax , Exulium add ChronoX and it is in XML.
Then, the File will here be named : FHDMaxChronoX.xml



So you can personalize with your name or place, don't forget to rename the ChronoX

2-Colors, Fonts, sizes and languages: StylisT

Sablure can now customize the colors of substantive text, fonts, and font sizes of the various elements and language
Each element is definable, you compose your presentation ideal
The list of colors is in DocStoR/couleurs.txt
And you will find a program to list your fonts in DocStoR/Polices
For bold type Bold = 'bold'
Bold ='' for normal text
The texts and language are fully defined in the file LanGage.xml



3-Internationalization:

it is possible to adapt sablures for all computer languages, why there is a encoding.xml file in the directory stylist.xml or you can change the encoding used. you will also need to change each xml file in the encoding chosen. Functionality untested. You can submit your files to contact@sablures.net

4-Attributes and lists:

Version 0.2.1 to 0.2.6 provides polymorphism it is you who are defining and identifying the lists they pre-present.

Here's how a works:

In the InCluD folder of the WokLaB you will find a file named InCluD.xml :



The NemFicXML contains filenames (without. Xml) NodeName attribute contains the name of the node * of this file (attention is also the name that will be used in the consolidation of extraction: Dozier here:



TiP attribute identifies the group, TiP GrouP is the general type of ID and TiP Master identifier identifies what is the stain itself, attention: there can be a TiP Master and can not be NodeName "Tache"

*node : in include.xml for exemple the name of node is IncluD

Then you can draw up a pre-list (you can always enter new values) in those famous files,

ex : the file of Taches BetaList



Note that the list is always constituted by the attribute Nam

5-Features emerged to version 0.2.8:
Version 0.2.8 brings a new feature, for example the change in price, place, person at the bar spots a list box to select the list and another list box allows you to select the attribute to change a button on the right applies the change.
Note: This change on the fly as the 0.3.8 version of the spot ends with the old attributes and starts a new spot for the new attributes for coherence in the extractions.

5-Features emerged to version 0.2.8:
Version 0.2.8 brings a new feature, for example the change in price, place, person at the bar spots a list box to select the list and another list box allows you to select the attribute to change a button on the right applies the change.
Note: This change on the fly as the 0.3.8 version of the spot ends with the old attributes and starts a new spot for the new attributes for coherence in the extractions.

Here you can customize and pre-fill a substantive your exulium

Good work

http://www.sablures.net
contact@sablures.net
+ 33 (0) 674781280

Funded by the Cabinet EURL Christian Roche http://www.cabinet-roche.com/